

# Rotule SI FSLX-08-DUNLOP - FSLX-08-DUNLOP

https://www.123roulement.com/roulement-palier/rotule/si/fslx-08-dunlop

FEMALE ROD ENDS 



**FSLX SERIES**

**Description:**  
FSLX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate  
Inner Ring: Steel 070M02, Zinc Plated and Clear Trivalent Passivate  
Ball: Bearing Steel 100Cr6, Case Hardened and Electroless Nickel Plated  
Liner: High Strength PTFE Composite

**Features:**  
Metric & Imperial thread & bore sizes, low friction, heavy duty high shock loads, extended wear life, no maintenance.

**Temperature Range:**  
-200°C to +240°C

**Possible Applications:**  
Motorsport and heavy industrial mechanical applications.

**Specification:**  
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-08		1/2	1/2 UNF	0.425	0.500	1.375	2.125	1.187	0.750	42000

**Interchange table**

Dunlop	Aurora	Fluro
FSLX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSLX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060556196
Diam. intérieur	12.7 mm
Diam. intérieur	1/2" inch
Diam. extérieur	34.925 mm
Diam. extérieur	1 3/8" inch
Epaisseur	15.875 mm
Epaisseur	5/8" inch
Type	SI
Filetage	Filetage à gauche
Lubrification	NA
Charge statique	42 kN
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE