


Rotule GE GE80-FW-DUNLOP - GE80-FW-DUNLOP

<https://www.123roulement.com/roulement-palier/rotule/ge/ge80-fw-dunlop>

SPHERICAL BEARINGS 



SPHERICAL BEARINGS




GE FW SERIES

Description:
GE-FW Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electro-less nickel plated. Liner: PTFE fabric. Seals: Polyurethane

Features:
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications:
Medium/Heavy Industrial/
mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control

Temperature Range:
-53°C to +121°C

Specification:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened Race: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Ball: PTFE Fabric

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE80FW		80	75	50	130	2,300,000

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060557353
Diam. intérieur	80 mm
Diam. extérieur	75 mm
Epaisseur	50 mm
Type	GE
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE