


## Rotule GE

### GE100-FW-DUNLOP - GE100-FW-DUNLOP

https://www.123roulement.com/roulement-palier/rotule/ge/ge100-fw-dunlop

SPHERICAL BEARINGS

**GE FW SERIES**

**Description:**  
GE-FW-Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the balls and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction, they do not require maintenance.

**Material Specifications:**  
Outer ring: Bearing steel 100Cr6, case hardened. Ball: Bearing steel 100Cr6, case hardened and electroless nickel plated. Liner: PTFE fabric. Seals: Polyurethane.

**Features:**  
Metric bore sizes  
Low friction  
High shock loads  
Extended wear life  
No maintenance

**Possible Applications:**  
Medium/heavy industrial mechanical applications  
Construction equipment  
Agricultural equipment  
Recreational vehicles  
High precision motion control.

**Temperature Range:**  
-52°C to +121°C

**Specification:**  
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened      Race: Bearing Steel 100Cr6, Case Hardened and Electroless Nickel Plated

Ball: PTFE Fabric

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE100FW		100	85	95	160	3,075,000

## CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060557391
Diam. intérieur	100 mm
Diam. extérieur	160 mm
Épaisseur	85 mm
Type	GE
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE