

Rotule GE GE300-ES-2RS-DUNLOP - GE300-ES-2RS-DUNLOP

<https://www.123roulement.com/roulement-palier/rotule/ge/ge300-es-2rs-dunlop>

SPHERICAL BEARINGS **DUNLOP**

GEZ ES SERIES



Description:
GEZ-ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race sliding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seats: Polyurethane.

Features:
Metric bore sizes.
Low cost.
Maintenance required.
Up to 140mm bore sizes available.

Possible Applications:
Light to heavy industrial/mechanical applications
Construction equipment
Agricultural equipment
Hydraulic applications

Temperature Range:
-34°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂

Balls: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seats: Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GEZ300ES-2RS	3	66.675	57.150	120.65	1,500,000

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060558312
Diam. intérieur	76.2 mm
Diam. extérieur	120.65 mm
Épaisseur	66.67 mm
Type	GE
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE