

Rotule GE GE40-UK-DUNLOP - GE40-UK-DUNLOP

<https://www.123roulement.com/roulement-palier/rotule/ge/ge40-uk-dunlop>

SPHERICAL BEARINGS 





GE UK SERIES

Description:
GE UK Series is our 2-piece metric range of general purpose spherical plain bearings incorporating a thin PTFE fabric between the ball and the outer ring, suitable for high shock loads and medium to heavy industrial/mechanical load applications requiring low friction. They do not require maintenance.

Material Specifications:
Outer ring: Bearing steel 100Cr6 and stainless steel 316, case hardened.
Ball: Bearing steel 100Cr6 case hardened and electro-less nickel plated and stainless steel 440C. Liner: High temperature PTFE composite.
Seals: Polyurethane.

Features
Metric bore sizes
Low friction
High shock loads
Extended wear life
No maintenance

Possible Applications
Medium-heavy industrial mechanical applications
Construction equipment
Agricultural equipment
Recreational vehicles
High precision motion control

Temperature Range
-200°C to +260°C
Specification
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened **Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Liner: High Temperature PTFE Composite

Part No. Unsized	Part No. Sized	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
GE40UK		40	28	22	62	290,000

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060558510
Diam. intérieur	40 mm
Diam. extérieur	62 mm
Epaisseur	28 mm
Type	GE
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE