

Rotule SA FSX-12-10-DUNLOP - FSX-12-10-DUNLOP

<https://www.123roulement.com/roulement-palier/rotule/sa/fsx-12-10-dunlop>

FEMALE ROD ENDS



FSX SERIES

Description:
FSX series is two 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate
Inner Ring: Steel 070M00, Zinc Plated and Clear Trivalent Passivate
Ball: Bearing Steel 100Cr6, Case Hardened and Electroless Nickel Plated
Liner: High Strength PTFE Composite

Features:
Metric & Imperial thread & bore sizes, low friction, heavy duty high shock loads, extended wear life, no maintenance.

Temperature Range:
-200°C to +240°C

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Specification:
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSX-12-10		5/8	3/4 UNF	0.875	0.687	2.000	2.875	1.750	1.000	9300

Interchange table

Dunlop	Aurora	Fluro
FSX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060558701
Diam. intérieur	15.875 mm
Diam. intérieur	5/8" inch
Diam. extérieur	50.8 mm
Diam. extérieur	2" inch
Epaisseur	22.225 mm
Epaisseur	7/8" inch
Type	SA
Filetage	Filetage à droite
Lubrification	NA
Charge statique	93.5 kN
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE