

## Roulement conique 795-792-TIMKEN - 795-792-TIMKEN

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/795-792-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
120.650	206.375	47.625	27900	1.10	8000	7700	1.27	93000	708 702	
4.750	8.1250	1.8750	85000		22000	17300		120000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>				A <sub>3</sub> <sup>(1)</sup>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
47.625	94.925	-1.8	3.3	134.8	126.8	3.3	196.8	186.0	6.3	2.8	358.4	62.0	0.1269	6.34
1.8750	1.3750	-0.07	0.13	5.28	5.47	0.13	7.72	7.32	0.21	0.11				13.89

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952092560
Diam. intérieur	120.65 mm
Diam. extérieur	206.38 mm
Épaisseur	47.63 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE