

Douille à aiguilles BA1416-Z-IKO - BA1416-Z-IKO

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/douille/ba1416-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed	Assembled inner ring
<i>F_{sw}</i>	<i>D</i>	<i>C</i>	Shaft dia. <i>d</i>		Housing bore dia. <i>D_h</i>	<i>C</i>	<i>C₀</i>	rpm		
			Max.	Min.	Max.	Min.	N	N		
22,025 (0.86)	28,575 (1.12)	25,40 (1.000)	2,5	22,225 (0.875)	28,567 (1.124)	28,566 (1.124)	17600	30500	18000	IRB 1016

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3616060603326
Diam. intérieur	22.225 mm
Diam. extérieur	28.575 mm
Epaisseur	25.4 mm
Vitesse limite	18000 rpm
Charge dynamique	17.6 kN
Charge statique	30.5 kN
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE