


## Rondelle ondulée fendue

**SWSW-114.30-101.35-0.76-5-SS - SWSW-114.30-101.35-0.76-5-SS**

<https://www.123roulement.com/accessoire/rondelle/rondelle-ondulee-fendue/sws-114.30-101.35-0.76-5-ss>

Do = Outside diameter (max) (mm)  
Di = Inside diameter (min) (mm)  
t = Thickness (mm)  
H = Free height approx.  
H1 = Load at height  
L1 = Load at L1 (+/-15 % Newton)  
Db = Bearing's outside diameter  
Dh = Free fit in hole diameter  
Dr = Free fit over hole diameter  
N = Number of waves



Split Wave Spring Washers

Part Number	Di (mm)	t (mm)	L1 (N)	H1 (mm)	Do (mm)	N	H (mm)
WWG04500230725	101,35	0,76	320,272	2,769	114,30	5	5,84

## CARACTÉRISTIQUES PRODUIT

Marque	GEN
Diam. intérieur	101.35 mm
Diam. intérieur	3.99" inch
Epaisseur	0.76 mm
Epaisseur	0.03" inch
Matière	INOX
Conditionnement	1
Charge à L1	320.272 N
Charge en hauteur	2.769
Diamètre extérieur (max)	114.3 mm
Diamètre extérieur (max)	4 1/2" inch
Nombre d'ondes	5

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE