


Rondelle ondulée fendue

SWSW-161.92-148.84-0.76-6-SS - SWSW-161.92-148.84-0.76-6-SS

<https://www.123roulement.com/accessoire/rondelle/rondelle-ondulee-fendue/sws-161.92-148.84-0.76-6-ss>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (+/-15 % Newton)
DB = Bearing's outside diameter
Dh = Free fit in hole diameter
De = Free fit over hole diameter
N = Number of waves



Split Wave Spring Washers

Part Number	Di (mm)	t (mm)	L1 (N)	H1 (mm)	Do (mm)	N	H (mm)
WWG0637035000B	148,84	0,76	444,822	3,175	161,92	6	9,89

CARACTÉRISTIQUES PRODUIT

Marque	GEN
Diam. intérieur	148.84 mm
Epaisseur	0.76 mm
Matière	INOX
Conditionnement	1
Charge à L1	444.82 N
Charge en hauteur	3.175
Diamètre extérieur (max)	161.92 mm
Nombre d'ondes	6

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE