


Rondelle ondulée fendue

SWSW-165.10-151.89-0.76-6 - SWSW-165.10-151.89-0.76-6

<https://www.123roulement.com/accessoire/rondelle/rondelle-ondulee-fendue/swsw-165.10-151.89-0.76-6>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (±15 % Newton)
DB = Bearing's outside diameter
Dh = Free fit in hole diameter
Dr = Free fit over hole diameter
N = Number of waves



Split Wave Spring Washers

| Part Number | Di (mm) | t (mm) | L1 (N) | H1 (mm) | Do (mm) | N | H (mm) |
|---------------|---------|--------|---------|---------|---------|---|--------|
| WWG0650039002 | 151.89 | 0.76 | 453.719 | 3.175 | 165.10 | 6 | 9.91 |

CARACTÉRISTIQUES PRODUIT

| | |
|--------------------------|-----------|
| Marque | GEN |
| Diam. intérieur | 151.89 mm |
| Epaisseur | 0.76 mm |
| Matière | ACIER |
| Conditionnement | 1 |
| Charge à L1 | 453.719 N |
| Charge en hauteur | 3.175 |
| Diamètre extérieur (max) | 165.1 mm |
| Nombre d'ondes | 6 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE