


Joint SPI

15005-SKF - 15005-SKF

<https://www.123roulement.com/joint-etancheite/joint/joint-spi/15005-skf>

Joint d'étanchéité radiaux pour applications industrielles générales

|                          |                                                          |    |
|--------------------------|----------------------------------------------------------|----|
| Type of outside diameter | Metal-cased with sealant coating on the outside diameter |    |
| Lip material             | Nitrile rubber (NBR)                                     |    |
| Seal design              | CRWA1                                                    |    |
| d <sub>1</sub>           | 38.1                                                     | mm |
| D                        | 60.3                                                     | mm |
| b                        | 7.95                                                     | mm |



|                                      |      |            |
|--------------------------------------|------|------------|
| Application and operating conditions |      |            |
| Operating temperature                | min. | -40 °C     |
| Operating temperature                | max. | 100 °C     |
| Shaft speed                          | max. | 3360 r/min |
| Shaft surface speed                  | max. | 6.74 m/s   |

CARACTÉRISTIQUES PRODUIT

|                 |             |
|-----------------|-------------|
| Marque          | SKF         |
| N° Ean13        | 85311015158 |
| Diam. intérieur | 38.1 mm     |
| Diam. extérieur | 60.3 mm     |
| Epaisseur       | 7.95 mm     |
| Poids           | 24 g        |
| Conditionnement | 1           |
| Norme           | Sans norme  |

[contact@123roulement.com](mailto:contact@123roulement.com)  
03 59 36 04 90  
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE