


## Palier - 2 fixations P2BSS-40M-YTPSS-SKF - P2BSS-40M-YTPSS-SKF

<https://www.123roulement.com/roulement-palier/paliers/palier-fonte-2/p2bss-40m-ytpss-skf>

Données de calcul		
Charge dynamique de base	C	24.7 kN
Charge statique de base	C <sub>0</sub>	19 kN
Limite de fatigue	P <sub>0</sub>	0.8 kN
Vitesse limite		2800 rpm
Compliance with standard		Not standardized
Matériau		Stainless steel
Sealing solution		Outer seals
Dimensions		
	d	40 mm
	d <sub>1</sub>	51.8 mm
	A	48 mm
	A <sub>1</sub>	30 mm
	A <sub>2</sub>	21.5 mm
	B	49.2 mm
	B <sub>1</sub>	10 mm
	H	99 mm
	H <sub>1</sub>	49.2 mm
	H <sub>2</sub>	19 mm
	J	135.5 mm
	J <sub>1</sub>	max. 146 mm
	J <sub>2</sub>	min. 135 mm
	L	174.5 mm
	N	24.5 mm
	N <sub>1</sub>	14.5 mm
	S <sub>1</sub>	30.2 mm
Plats de centrage		
	G	12 mm
	G <sub>1</sub>	0.6 mm

## CARACTÉRISTIQUES PRODUIT

Marque	SKF
N° Ean13	3616060837707
Diamètre de l'arbre	40 mm
Diamètre de l'arbre	1.575" inch
Nb de fixation	2
Serrage	Bague de blocage excentrique
Entraxe de fixation	135.5 mm
Entraxe de fixation	5.335" inch
Matière	INOX
Poids	1990 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE