


## Roulement à aiguilles 17NQ3013D-JTEKT - 17NQ3013D-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/17nq3013d-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
17	—	30	13	—	10.0	10.5	25 000	17NQ3013D
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
d <sub>1</sub>	D <sub>1</sub>	r <sub>1</sub>	r	0.041	—			
max.	max.	max.	max.					
—	—	28	0.3					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3616060008190
Diam. intérieur	17 mm
Diam. extérieur	30 mm
Épaisseur	13 mm
Poids	40 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE