


## Roulement conique 57008-R-JTEKT - 57008-R-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/57008-r-jtekt>

Single-row tapered roller bearings  
metric series



**Koyo**

Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>	
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.		Oil lub.
20	47	15.25	14	12	25.8	25.5	9 000	12 000	57008R

Dimension series to ISO 355 (DIN 625)	Load center (mm)	Mounting dimensions (mm)						Constant e	Axial load factors			Reference Mass (kg)		
		d <sub>1</sub> min.	d <sub>1</sub> max.	D <sub>1</sub> min.	D <sub>1</sub> max.	S <sub>1</sub> min.	S <sub>1</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	Y <sub>2</sub>			
—	12.9	25.5	26	41.5	37	44	2	3	1	1	0.52	1.16	0.64	0.125

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400372
Diam. intérieur	20 mm
Diam. extérieur	47 mm
Épaisseur	15.25 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE