

Roulement conique 322-22-R-JTEKT - 322-22-R-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/322-22-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
22	50	19.25	18	15	36.8	41.6	8 100	11 000	322/22R					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d _α min.	d _α max.	D _α min.	D _α max.	S _α min.	S _α max.	r _α min.	r _α max.	Constant e	Axial load factors Y ₁	Axial load factors Y ₀	(Refer. 1) Mass (kg)	
—	14.0	27.5	29	44.5	41	46	2	4	1	1	0.37	1.00	0.88	0.178

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400433
Diam. intérieur	22 mm
Diam. extérieur	50 mm
Épaisseur	19.25 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE