

Roulement conique 303-22-XR-JTEKT - 303-22-XR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/303-22-xr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
22	56	17.25	16	13	1.5	1.5	36.3	36.6	7 700	10 000	303/22XR			
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _α min.	d _α max.	D _α min.	D _α max.	S _α min.	S _α max.	r _α min.	r _α max.		Y ₁	Y ₀		
—	15.7	30.5	31	47.5	44	52	3	4	1.5	1.5	0.59	1.02	0.56	0.210

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400440
Diam. intérieur	22 mm
Diam. extérieur	56 mm
Épaisseur	17.25 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE