

Roulement conique 322-28-R-JTEKT - 322-28-R-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/322-28-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
28	58	20.25	19	16	49.2	55.2	6 900	9 100			322/28R			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S _α min.	S _β min.	r _α min.	r _β min.		Y ₁	Y ₀		
—	15.0	33.5	35	52.5	49	54.5	2	4	1	1	0.37	1.60	0.88	0.244

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400532
Diam. intérieur	28 mm
Diam. extérieur	58 mm
Épaisseur	20.25 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE