

Roulement conique 302-32-R-JTEKT - 302-32-R-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/302-32-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
32	65	18.25	17	15	48.0	51.4	6 200	8 200	302/32R					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d ₁ min.	d ₂ max.	D ₁ min.	D ₂ min.	S _α min.	S _β min.	r _α min.	r _β min.	Constant e	Axial load factors Y ₁	Axial load factors Y ₀	(Refer. 1) Mass (kg)	
—	14.9	37.5	39	59.5	55	61	3	3	1	1	0.37	1.60	0.88	0.286

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400785
Diam. intérieur	32 mm
Diam. extérieur	65 mm
Épaisseur	18.25 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE