


## Roulement conique T2ED050-JTEKT - T2ED050-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/t2ed050-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
50	100	36	35	30	2.5	2.5	157	196	4 100	5 400	T2ED050			
Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>α</sub> min.	S <sub>β</sub> min.	r <sub>α</sub> max.	r <sub>β</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2ED	24.5	62	58	88	84	94	6	6	2	2	0.34	1.75	0.96	1.28

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250067303
Diam. intérieur	50 mm
Diam. extérieur	100 mm
Épaisseur	36 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE