

## Roulement conique 30319-JTEKT - 30319-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/30319-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
95	200	49.5	45	38	4	3	317	368	2 000	2 600	30319			
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>α</sub> min.	d <sub>α</sub> max.	D <sub>α</sub> min.	D <sub>α</sub> max.	S <sub>α</sub> min.	S <sub>α</sub> max.	r <sub>α</sub> min.	r <sub>α</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	39.8	113	118	186	172	186	5	11.5	3	2.5	0.35	1.73	0.95	6.32

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122354
Diam. intérieur	95 mm
Diam. intérieur	3.74" inch
Diam. extérieur	200 mm
Diam. extérieur	7.874" inch
Epaisseur	49.5 mm
Epaisseur	1.949" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE