

Roulement conique T2EE100-JTEKT - T2EE100-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/t2ee100-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | |
|--------------------------------------|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|----------------|---------------------------|------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | |
| 100 | 165 | 47 | 46 | 39 | 3 | 3 | 293 | 458 | 2 200 | 3 000 | T2EE100 | | |
| Dimension series to ISO 355 (Refer.) | Load center (mm) a | Mounting dimensions (mm) | | | | | | Constant e | Axial load factors | | (Refer.) Mass (kg) | | |
| 2EE | 35.1 | d ₁ min. | d ₂ max. | D ₁ max. | D ₂ min. | S _α min. | S _β min. | r _α max. | r _β max. | Y ₁ | Y ₀ | 3.86 | |
| | | 114 | 112 | 151 | 145 | 157 | 7 | 8 | 2.5 | 2.5 | 0.32 | 1.88 | 1.04 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952410524 |
| Diam. intérieur | 100 mm |
| Diam. intérieur | 3.937" inch |
| Diam. extérieur | 165 mm |
| Diam. extérieur | 6.496" inch |
| Epaisseur | 47 mm |
| Epaisseur | 1.85" inch |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE