

Roulement conique 30320-D-JTEKT - 30320-D-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/30320-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
100	215	51.5	47	34	318	374	1500	2100			30320D

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d ₁ min.	d ₁ max.	D ₁ min.	D ₁ max.	S ₁ min.	S ₁ max.	r ₁ min.	r ₁ max.	r ₂ min.	r ₂ max.		Y ₁	Y ₀	
—	65.9	118	121	201	183	204	5	17	3	2.5	0.81	0.74	0.41	8.02	

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122415
Diam. intérieur	100 mm
Diam. extérieur	215 mm
Épaisseur	51.5 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE