

## Roulement conique 31320-JR-JTEKT - 31320-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/31320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
100	215	56.5	51	35	4	3	373	459	1 500	2 200	31320JR

  

Dimension series to ISO995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>α</sub> min.	S <sub>β</sub> min.	r <sub>α</sub> max.	r <sub>β</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
7GB	67.7	118	120	201	183	202	6	17.5	3	2.5	0.83	0.73	0.40	8.72

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122828
Diam. intérieur	100 mm
Diam. intérieur	3.937" inch
Diam. extérieur	215 mm
Diam. extérieur	8.465" inch
Epaisseur	56.5 mm
Epaisseur	2.224" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE