

## Roulement conique 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                     |                     | Basic load ratings (kN) |                     |                     |                     | Limiting speeds (min <sup>-1</sup> ) |            | Bearing No. <sup>1)</sup> |                |                      |      |
|--|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                   | C                   | C <sub>r</sub>          | C <sub>0r</sub>     | C <sub>90</sub>     | C <sub>100</sub>    | Grease lub.                          | Oil lub.   |                           |                |                      |      |
| 100                                    | 215                | 77.5                     | 73                  | 60                  | 579                     | 783                 | 1 800               | 2 400               |                                      |            | 32320JR                   |                |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                     |                     |                         |                     |                     |                     |                                      | Constant e | Axial load factors        |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1</sub> min.      | d <sub>2</sub> max. | D <sub>1</sub> min. | D <sub>2</sub> max.     | S <sub>1</sub> min. | S <sub>2</sub> max. | r <sub>1</sub> min. | r <sub>2</sub> max.                  |            | Y <sub>1</sub>            | Y <sub>0</sub> |                      |      |
| 26D                                    | 53.9               | 118                      | 123                 | 201                 | 177                     | 200                 | 8                   | 17.5                | 3                                    | 2.5        | 0.35                      | 1.74           | 0.96                 | 13.0 |

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952410623 |
| Diam. intérieur | 100 mm        |
| Diam. extérieur | 215 mm        |
| Épaisseur       | 77.5 mm       |
| Conditionnement | 1             |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE