

Roulement conique 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/32320-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | |
|--|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|------------|-------------------------------|---------------------|-----------|
| d | D | T | B | C | C _r | C _{0r} | C _{0e} | C _{0a} | Grease lub. | Oil lub. | | | |
| 100 | 215 | 77.5 | 73 | 60 | 579 | 783 | 1 800 | 2 400 | | | 32320JR | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors (Refer. 1) | | Mass (kg) |
| 260 | 53.9 | d ₁ min. | d ₂ max. | D ₁ max. | D ₂ min. | S ₁ min. | S ₂ min. | r ₁ max. | r ₂ max. | 0.35 | Y ₁ 1.74 | Y ₀ 0.96 | 13.0 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952410623 |
| Diam. intérieur | 100 mm |
| Diam. extérieur | 215 mm |
| Épaisseur | 77.5 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE