

## Roulement conique 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/32320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.					
100	215	77.5	73	60	579	783	1 800	2 400			32320JR				
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1</sub> min.	d <sub>1</sub> max.	D <sub>1</sub> min.	D <sub>1</sub> max.	S <sub>1</sub> min.	S <sub>1</sub> max.	r <sub>1</sub> min.	r <sub>1</sub> max.	r <sub>2</sub> min.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
26D	53.9	118	123	201	177	200	8	17.5	3	2.5	0.35	1.74	0.96	13.0	

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952410623
Diam. intérieur	100 mm
Diam. extérieur	215 mm
Epaisseur	77.5 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE