


## Roulement conique 32321-JR-JTEKT - 32321-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/32321-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>		
d	D	T	B	C	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.					
105	225	81.5	77	63	4	635	866	1 800	2 300			32321JR		
Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>α</sub> min.	S <sub>β</sub> min.	r <sub>α</sub> min.	r <sub>β</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
26D	56.1	123	128	211	185	209	8	18.5	3	2.5	0.35	1.74	0.96	14.9

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952411217
Diam. intérieur	105 mm
Diam. extérieur	225 mm
Épaisseur	81.5 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE