

## Roulement conique 30324-JR-JTEKT - 30324-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/30324-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>0e</sub>	Grease lub.	Oil lub.					
120	260	59.5	55	46	569	714		1 500	2 000	30324JR				
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> min.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2GB	50.2	138	152	246	221	239	10	13.5	3	2.5	0.35	1.74	0.96	14.5

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952411439
Diam. intérieur	120 mm
Diam. extérieur	260 mm
Épaisseur	59.5 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE