

Roulement conique 32324-JR-JTEKT - 32324-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/32324-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | | |
|--|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|--------------------------------------|---------------------|---------------------------|---------------------|----------------|----------------------|----------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 120 | 260 | 90.5 | 86 | 69 | 800 | 1 110 | 1 500 | 2 000 | 32324JR | | | | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | | |
| | | d ₁ min. | d ₂ max. | D ₁ max. | D ₂ min. | S ₁ min. | S ₂ min. | r ₁ max. | | r ₂ max. | Y ₁ | | Y ₀ | |
| 260 | 62.7 | 138 | 148 | 246 | 213 | 239 | 9 | 21.5 | 3 | 2.5 | 0.35 | 1.74 | 0.96 | 22.2 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 4549250125355 |
| Diam. intérieur | 120 mm |
| Diam. extérieur | 260 mm |
| Épaisseur | 90.5 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE