


## Roulement conique 32056-JR-JTEKT - 32056-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/32056-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
280	420	87	87	65	5	4	1 200	2 280	720	960	32056JR			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>3</sub> min.	r <sub>4</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
4FC	91.1	302	305	402	370	402	14	22	4	3	0.46	1.31	0.72	41.7

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250123832
Diam. intérieur	280 mm
Diam. extérieur	420 mm
Épaisseur	87 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE