

## Roulement conique 30256-JTEKT - 30256-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/30256-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
280	500	89	80	67	1260	1920	610	610	30256					
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> max.	r <sub>2</sub> max.	Constant e	Axial load factors Y <sub>1</sub>	Y <sub>0</sub>	(Refer.) Mass (kg)	
—	96.2	308	325	478	440	475	14	21	5	4	0.42	1.44	0.79	67.5

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952412030
Diam. intérieur	280 mm
Diam. extérieur	500 mm
Épaisseur	89 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE