

Roulement conique 31326-JR-JTEKT - 31326-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/31326-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|--|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | | | | |
| 130 | 280 | 72 | 66 | 44 | 589 | 748 | 1 200 | 1 600 | | | 31326JR | | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d ₁ min. | d ₂ max. | D ₁ max. | D ₂ min. | S ₁ min. | S ₂ min. | r ₁ max. | r ₂ max. | | Y ₁ | Y ₀ | | |
| 7GB | 87.3 | 152 | 155 | 262 | 236 | 261 | 7 | 23 | 4 | 3 | 0.83 | 0.73 | 0.40 | 18.9 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952419619 |
| Diam. intérieur | 130 mm |
| Diam. extérieur | 280 mm |
| Épaisseur | 72 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE