

Roulement conique 32032-JR-JTEKT - 32032-JR-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/32032-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | |
|---------------------------------------|--------------------|--------------------------|---------------------|---------------------|------------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|--------------------|---------------------------|----------------------|------|
| d | D | T | B | C | r ₁ min. | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | |
| 160 | 240 | 51 | 51 | 36 | 3 | 2.5 | 440 | 758 | 1 400 | 1 900 | 32032JR | | | |
| Dimension series to ISO355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _α min. | d _α max. | D _α min. | D _α max. | S _α min. | S _α max. | r _α min. | r _α max. | | Y ₁ | Y ₀ | | |
| 4EC | 52.1 | 174 | 175 | 228 | 213 | 231 | 8 | 13 | 2.5 | 2 | 0.46 | 1.31 | 0.72 | 7.75 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952421230 |
| Diam. intérieur | 160 mm |
| Diam. extérieur | 240 mm |
| Epaisseur | 51 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE