

## Roulement conique L44640R-L44610-JTEKT - L44640R-L44610-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/l44640r-l44610-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1 min.</sub>	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10v</sub>	Grease lub.	Oil lub.
23.812	50.292	14.224	14.732	10.668	1.6	1.2	31.2	37.0	7 800	10 000

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a max.</sub>	<i>r</i> <sub>b max.</sub>	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
L44640R	L44610	10.8	30.5	28.5	44.5	47.0	1.6	1.2	0.37	1.60	0.88	0.099	0.034

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952425559
Diam. intérieur	23.812 mm
Diam. intérieur	15/16" inch
Diam. extérieur	50.292 mm
Diam. extérieur	1.98" inch
Epaisseur	14.224 mm
Epaisseur	0.56" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE