

## Roulement conique 17098-17244-JTEKT - 17098-17244-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/17098-17244-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r$ max.	$r_1$ min.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
24.981	62.000	16.002	16.566	14.288	1.6	1.6	38.0	40.6	6 700	8 900

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
17098	17244	12.7	33.0	30.5	54.0	57.0	1.6	1.6	0.38	1.57	0.86	0.162	0.090

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952425597
Diam. intérieur	24.981 mm
Diam. extérieur	62 mm
Épaisseur	16.002 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE