

## Roulement conique 2682-2631-JTEKT - 2682-2631-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/2682-2631-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r max.	r1 min.	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
26.162	66.421	23.812	25.433	19.050	1.6	1.2	67.0	75.2	6 500	8 700

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
2682	2631	13.9	34.5	32.0	58.0	60.0	1.6	1.2	0.25	2.36	1.30	0.268	0.163

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952425740
Diam. intérieur	26.162 mm
Diam. extérieur	66.421 mm
Épaisseur	23.421 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE