

## Roulement conique 16137-16284-JTEKT - 16137-16284-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/16137-16284-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



| Boundary dimensions (mm) |          |          |          |          |                          |                                       | Basic load ratings (kN) |                        | Limiting speeds (min <sup>-1</sup> ) |          |
|--------------------------|----------|----------|----------|----------|--------------------------|---------------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i>                 | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> <sub>max.</sub> | <i>r</i> <sub>1</sub> <sub>min.</sub> | <i>C</i> <sub>r</sub>   | <i>C</i> <sub>10</sub> | Grease lub.                          | Oil lub. |
| 34.925                   | 72.238   | 20.638   | 20.638   | 15.875   | 3.6                      | 1.2                                   | 49.7                    | 61.3                   | 5 600                                | 7 400    |

  

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |                       |                       |                       |                                       |                                       | Constant | Axial load factors    |                       | (Refer.) Mass (kg) |            |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|---------------------------------------|---------------------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring  | Outer ring | <i>a</i>         | <i>d</i> <sub>a</sub>    | <i>d</i> <sub>b</sub> | <i>D</i> <sub>a</sub> | <i>D</i> <sub>b</sub> | <i>r</i> <sub>a</sub> <sub>max.</sub> | <i>r</i> <sub>b</sub> <sub>max.</sub> | <i>e</i> | <i>Y</i> <sub>1</sub> | <i>Y</i> <sub>2</sub> | Inner ring         | Outer ring |
| 16137       | 16284      | 16.6             | 46.5                     | 40.5                  | 63.0                  | 67.0                  | 3.6                                   | 1.2                                   | 0.40     | 1.49                  | 0.82                  | 0.236              | 0.144      |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952426310 |
| Diam. intérieur | 34.925 mm     |
| Diam. extérieur | 72.238 mm     |
| Épaisseur       | 20.638 mm     |
| Conditionnement | 1             |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE