


Roulement conique 02877-02820-JTEKT - 02877-02820-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/02877-02820-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
34.925	73.025	22.225	22.225	17.462	3.6	3.2	55.0	65.7	5 500	7 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
02877	02820	18.4	48.5	42.0	62.0	68.0	3.6	3.2	0.45	1.32	0.73	0.262	0.158

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952426327
Diam. intérieur	34.925 mm
Diam. intérieur	1 3/8" inch
Diam. extérieur	43.025 mm
Diam. extérieur	1.694" inch
Epaisseur	22.225 mm
Epaisseur	7/8" inch
Poids	420 g
Conditionnement	1
Norme	Sans norme

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE