

Roulement conique 3479-3420-JTEKT - 3479-3420-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/3479-3420-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|---------------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ _{max.} | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 36.512 | 79.375 | 29.370 | 29.771 | 23.812 | 0.8 | 3.2 | 87.4 | 105 | 5 200 | 6 900 |

| Bearing No. | | Load center (mm) <i>a</i> | Mounting dimensions (mm) | | | | | | Constant <i>e</i> | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|---------------------------|--------------------------|-----------------------|-----------------------|-----------------------|---------------------------------------|---------------------------------------|-------------------|-----------------------|-----------------------|--------------------|------------|
| Inner ring | Outer ring | | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a _{max.} | <i>r</i> _b _{max.} | | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 3479 | 3420 | 20.8 | 45.5 | 44.5 | 67.0 | 74.0 | 0.8 | 3.2 | 0.37 | 1.64 | 0.90 | 0.429 | 0.259 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952426488 |
| Diam. intérieur | 36.512 mm |
| Diam. extérieur | 79.375 mm |
| Épaisseur | 29.37 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE