


## Roulement conique 2788R-2735X-JTEKT - 2788R-2735X-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/2788r-2735x-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r	r <sub>1</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
38.100	73.025	23.812	25.654	19.050	3.6	0.8	74.1	92.2	5 400	7 200

Bearing No.		Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.		Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
2788R	2735X	15.9	50.0	43.5	66.0	69.0	3.6	0.8	0.30	1.98	1.09	0.308	0.134

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952426600
Diam. intérieur	38.1 mm
Diam. extérieur	73.025 mm
Épaisseur	23.812 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE