


## Roulement conique 525-522-JTEKT - 525-522-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/525-522-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> <sub>min.</sub>	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
38.100	101.600	34.925	38.088	26.988	3.6	3.2	131	159	4 000	5 300

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> <sub>max.</sub>	<i>r</i> <sub>b</sub> <sub>max.</sub>		<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
525	522	22.2	54.0	48.0	89.0	95.0	3.6	3.2	0.29	2.10	1.16	1.05	0.411

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952426686
Diam. intérieur	38.1 mm
Diam. extérieur	101.6 mm
Épaisseur	34.925 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE