


Roulement conique 4395-4335-JTEKT - 4395-4335-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/4395-4335-jtekt>

Single-row tapered roller bearings
inch series Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|---------------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ _{min.} | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 42.070 | 90.488 | 39.688 | 40.386 | 33.338 | 3.6 | 3.2 | 132 | 169 | 4 500 | 6 000 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|---------------------------------------|---------------------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a _{max.} | <i>r</i> _b _{max.} | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 4395 | 4335 | 25.6 | 58.0 | 51.0 | 77.0 | 85.0 | 3.6 | 3.2 | 0.28 | 2.11 | 1.16 | 0.751 | 0.459 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952426969 |
| Diam. intérieur | 42.07 mm |
| Diam. extérieur | 90.488 mm |
| Épaisseur | 39.688 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE