

Roulement conique 355A-354A-JTEKT - 355A-354A-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/355a-354a-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
44.450	85.000	20.638	21.692	17.462	0.8	1.2	71.8	81.7	4 600	6 200

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg) Inner ring Outer ring	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₂		
355A	354A	15.5	51.0	50.0	77.0	80.0	0.8	1.2	0.31	1.96	1.08	0.344	0.160

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952427072
Diam. intérieur	44.45 mm
Diam. intérieur	1 3/4" inch
Diam. extérieur	85 mm
Diam. extérieur	3.346" inch
Epaisseur	20.638 mm
Epaisseur	13/16" inch
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE