


Roulement conique 359A-354A-JTEKT - 359A-354A-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/359a-354a-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
46.038	85.000	20.638	21.692	17.462	3.6	1.2	71.8	81.7	4 600	6 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
359A	354A	15.5	57.0	51.0	77.0	80.0	3.6	1.2	0.31	1.96	1.08	0.323	0.160

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952427317
Diam. intérieur	46.038 mm
Diam. extérieur	85 mm
Épaisseur	20.638 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE