


## Roulement conique 2984-2924-JTEKT - 2984-2924-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/2984-2924-jtekt>

Single-row tapered roller bearings  
inch series



**Koyo**

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
46.038	85.000	25.400	25.608	20.638	3.6	1.2	80.0	106	4 600	6 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
<b>2984</b>	<b>2924</b>	18.9	58.0	52.0	76.0	80.0	3.6	1.2	0.35	1.73	0.95	0.389	0.220

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952427331
Diam. intérieur	46.038 mm
Diam. intérieur	1 13/16" inch
Diam. extérieur	85 mm
Diam. extérieur	3.346" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE