

Roulement conique 66589-66520-JTEKT - 66589-66520-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/66589-66520-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|------------------|------------------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r_{max} | r_{min} | C_r | C_{10} | Grease lub. | Oil lub. |
| 59.972 | 122.238 | 33.338 | 31.750 | 23.812 | 0.8 | 3.2 | 128 | 153 | 3 300 | 4 300 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|------------|------------|--------------------|-------|--------------------|------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| 66589 | 66520 | 35.4 | 74.0 | 73.0 | 105.0 | 116.0 | 0.8 | 3.2 | 0.67 | 0.90 | 0.50 | 1.11 | 0.551 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952428246 |
| Diam. intérieur | 59.972 mm |
| Diam. extérieur | 122.238 mm |
| Épaisseur | 33.338 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE