


Roulement conique 6382-6320-JTEKT - 6382-6320-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/6382-6320-jtekt>

Single-row tapered roller bearings
inch series Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|----------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ min. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 63.500 | 135.755 | 53.975 | 58.007 | 44.450 | 4.3 | 3.2 | 286 | 357 | 3 000 | 4 000 |

| Bearing No. | | Load center (mm) <i>a</i> | Mounting dimensions (mm) | | | | | | Constant <i>e</i> | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------------------|--------------------------|-----------------------|-----------------------|-----------------------|----------------------------|----------------------------|----------------------|-----------------------|-----------------------|-----------------------|------------|
| Inner ring | Outer ring | | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 6382 | 6320 | 34.8 | 84.0 | 77.0 | 117.0 | 126.0 | 4.3 | 3.2 | 0.32 | 1.85 | 1.02 | 2.29 | 1.39 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952428512 |
| Diam. intérieur | 63.5 mm |
| Diam. extérieur | 135.755 mm |
| Épaisseur | 53.975 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE