


Roulement conique 39586-39520-JTEKT - 39586-39520-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/39586-39520-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
64.986	112.712	30.162	30.924	23.812	2.4	3.2	147	207	3 300	4 500

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
39586	39520	23.3	76.0	72.0	101.0	107.0	2.4	3.2	0.34	1.77	0.97	0.845	0.355

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428536
Diam. intérieur	64.986 mm
Diam. extérieur	112.712 mm
Épaisseur	30.162 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE