


## Roulement conique

### HM212049-HM212010-JTEKT - HM212049-HM212010-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/hm212049-hm212010-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
66.675	122.238	38.100	38.354	29.718	3.6	1.6	191	249	3 200	4 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
HM212049	HM212010	27.3	82.0	75.5	110.0	116.0	3.6	1.6	0.34	1.78	0.98	1.26	0.596

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428635
Diam. intérieur	66.675 mm
Diam. intérieur	2 5/8" inch
Diam. extérieur	122.238 mm
Diam. extérieur	4 13/16" inch
Epaisseur	38.1 mm
Epaisseur	1 1/2" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE